

Lightweight, telescopic masts with attached tripod for directional or omni-directional headloads

FT masts are typically field masts derived from the well-known QT mast range.

Easy and quick to deploy, manually or with handpump and supported with three foldable legs which are permanently attached to the mast.



Technical Details

Silent, smooth and easy operation



PHOTO SHOWS SFT-RM4-4/H MAST (MANUALLY EXTENDED)

The features that have made it such an attractive and useful piece of equipment are :

1. Aluminium alloy sections
2. Handpump (not for manually extended masts)
3. Field base
4. Leg clamp
5. Air-release screw (not for manually extended masts)
6. Section-clamping screws
7. Guy collar
8. Turning Collar
9. Quick-clamp for headload



PHOTO SHOWS SFT-RM4-4/HP MAST

Standard FT-RM Mast Range

Manually extended or with handpump

Rotatable FT-RM Mast Range (extended with handpump)

3" / 76,2mm BASE TUBE

Mast Model	Cat. No.	Retracted Height	Extended Height	Standard Finish	Max. Headload	Mast Guying Kit Cat. No.
3 section masts						
SFT-RM3-3/HP	27992	1,45 m	3,30 m	nato green	20,0 kg	33720/NG
4 section masts						
SFT-RM4-4/HP	33000	1,50 m	4,20 m	nato green	20,0 kg	33721/NG
5 section masts						
SFT-RM5-5/HP	33004	1,55 m	5,10 m	nato green	15,0 kg	33722/NG
6 section masts						
SFT-RM6-6/HP	33008	1,60 m	6,05 m	nato green	10,0 kg	33723/NG
SFT-RM9-6/HP	33020	2,05 m	8,80 m	nato green	10,0 kg	33726/NG
SFT-RM10-6/HP	33024	2,35 m	10,05 m	nato green	10,0 kg	33727/NG
7 section masts						
SFT-RM7-7/HP	33012	1,60 m	7,00 m	nato green	6,0 kg	33724/NG
SFT-RM11-7/HP	33028	2,30 m	11,05 m	nato green	4,5 kg	33728/NG
8 section masts						
SFT-RM8-8/HP	33016	1,65 m	7,95 m	nato green	4,5 kg	33725/NG
SFT-RM12-8/HP	33032	2,15 m	11,60 m	nato green	2,5 kg	33729/NG

Rotatable FT-RM Mast Range (manually extended)

3" / 76,2mm BASE TUBE

Mast Model	Cat. No.	Retracted Height	Extended Height	Standard Finish	Max. Headload	Mast Guying Kit Cat. No.
3 section masts						
SFT-RM3-3/H	33072	1,45 m	3,05 m	nato green	10,0 kg	33720/NG
4 section masts						
SFT-RM4-4/H	33074	1,45 m	4,05 m	nato green	10,0 kg	33721/NG
5 section masts						
SFT-RM5-5/H	33076	1,50 m	5,05 m	nato green	10,0 kg	33722/NG
6 section masts						
SFT-RM6-6/H	33078	1,55 m	6,00 m	nato green	10,0 kg	33723/NG

FT-RM Masts Mounting Accessories

FT-RM Mast Guying Kits

For all FT-RM Series masts is a Mast Guying Kit available consisting of Spikes, Canvas Top Cover, Pickets, Hammer, Radius Line, Top guys + Middle Guys (if applicable) and Accessory Bag.



PHOTO SHOWS "FT-RM KIT" VERSION WITH OPTIONAL MAST CARRYING BAG

FT-RM Mast Carrying Bags

The FT-RM Series masts are also available with an optional carrying bag to simplify transport or just for protection of the stored mast.

FT-RM Mast Carrying Bags for rotatable masts (extended with handpump)

Carrying Bag Models	Cat. No.
SFT-RM3-3/HP Bag	30221/NG
SFT-RM4-4/HP Bag	30222/NG
SFT-RM5-5/HP Bag	30222/NG
SFT-RM6-6/HP Bag	30223/NG
SFT-RM9-6/HP Bag	30225/NG
SFT-RM10-6/HP Bag	30228/NG
SFT-RM7-7/HP Bag	30224/NG
SFT-RM11-7/HP Bag	30228/NG
SFT-RM8-8/HP Bag	30224/NG
SFT-RM12-8/HP Bag	30226/NG

FT-RM Mast Carrying Bags for rotatable masts (manually extended)

Carrying Bag Models	Cat. No.
SFT-RM3-3/H Bag	30220/NG
SFT-RM4-4/H Bag	30221/NG
SFT-RM5-5/H Bag	30222/NG
SFT-RM6-6/H Bag	30222/NG

CLARK MASTS™

All details given in this publication are approximate and may be subject to change without notice.

Dealer :

ClarkMast-USA, LLC

2347 Romig Rd.,
Pottstown, PA 19464, USA
Phone: 1-610-804-7938
E-mail: sales@clarkmasts-usa.com

CLARK MASTS TEKSAM NV, Woudstraat 21, B-3600 Genk, Belgium

Tel : +32 (0)89 38 44 72 - Fax : +32 (0)89 38 61 41 - E-mail : info@teksam.be - Website : www.clarkmasts.be